

Dual-Lock™



Dual-Lock™

, , Dual-Lock™ 170 400.

Dual-Lock 400

Lock™, 400 ()

Dual-Lock 250

$$250 \quad (\sim 39 / .) , \quad , \\ 250.$$

Dual-Lock 170

170 170 (~ 26 / .).
Dual-Lock™ 400 (.) 170 Scotchmate™ Loop™

SJ-3540 Тип 250	,	Dual-Lock™	50°
SJ-3541	400	,	“ ”
SJ-3550	250	Dual-Lock™	VHB™,
SJ-3560	250	,	,
	:	,	,
●	95°	,	,
●	(,)
100%	.	.	,
●	95°	-20°	95°
●	30°	70°	,
●	(SJ-3560)		0%
●	SJ-3560		

()

Dual-Lock™



	SJ-3540	SJ-3541	SJ-3560	SJ-3550
(/)	/ -	- /	/ VHB	/ VHB
, ±0,5				
SJ-3540/SJ-3540			4,1	
SJ-3550/SJ-3550			5,8	
SJ-3560/SJ-3560			5,8	
^a (/)			>1000	
^b			1	

a

Dual-Lock 12

21° 50%

()		b	
22,2°	50%		
250 / 250		[]	[]
250 / 400	103		242-311
	309 ()		311-380
		400/ 400	

a

170/ 170.

b

305 /

SJ-3560

SJ-3560		CARC
		(Chemical agent resistant coating)
	254.5	1026.6

22° 50%			

a

280 , / 280 , / 400/ 400

b

14 22° 280 / 14 22° 280 /

60 2 I ()

SJ3540, 3541	-30°	50°	-30°	70°
SJ3550	-30°	70°	-30°	93°
SJ3560	-30°	70°	-30°	93°

SJ3551/3552

, 77 155 / 2 , , 7

93° ! 50°

Dual-Lock™



20° .
72- SJ3560. 48 SJ3541/3542 48

1359 1357F 3 Scotch-Grip™ 4693, 847,

! () ,

